


LOCATION MAP
(N.T.S.)


SUMMITT SEARTHWORKS

DERWENT WAY TRANSFER STATION LOT 3, PLAN 13803 & BLOCK 9, PLAN 2602 NEW WESTMINSTER, BC ISSUED FOR PERMIT

	DRAWING INDEX				
#	DESCRIPTION	STATUS	DATE	REVISION	
n/a	PROJECT COVER SHEET	n/a	n/a	n/a	
T00006D	TOPOGRAPHIC PLAN (BY HIGHMARK SURVEY AND ENGINEERING LTD.)	FOR REFERENCE ONLY			
03082-LA100	LEASE AREA PLAN	ISSUED FOR PERMIT	2019.07.18	E	
03082-01	GENERAL NOTES FOR CIVIL WORKS	ISSUED FOR PERMIT	2019.07.18	F	
03082-02	TESTHOLE LOCATION PLAN	ISSUED FOR PERMIT	2019.07.18	F	
03082-03	TOPSOIL STRIPPING AND GRUBBING PLAN	ISSUED FOR PERMIT	2019.07.18	G	
03082-04	GENERAL ARRANGEMENT — SITE PLAN	ISSUED FOR PERMIT	2019.07.18	F	
03082-05	GRADING PLAN — FINISHED GRADE	ISSUED FOR PERMIT	2019.07.18	F	
03082-06	SITE PROFILES AND SECTIONS	ISSUED FOR PERMIT	2019.07.18	F	
03082-07	RETAINING WALL DETAILS	ISSUED FOR PERMIT	2019.07.18	F	
03085-08	STORM PIPE DRAINAGE PLAN	ISSUED FOR PERMIT	2019.07.18	F	
03085-10	VEHICLE ROUTING — SITE ENTRY / EXIT	ISSUED FOR PERMIT	2019.07.18	F	
03085-12	LANDSCAPING PLAN	ISSUED FOR PERMIT	2019.07.18	G	
03085-13	SURVEY MONITORING POINT PLAN	ISSUED FOR PERMIT	2019.07.18	F	
03085-100	BARGE LOADING MARINE FACILITY PLAN — GENERAL ARRANGEMENT	ISSUED FOR PERMIT	2019.07.18	D	
03085-101	OPERATIONAL LOADING — GENERAL ARRANGEMENT	ISSUED FOR PERMIT	2019.07.18	В	
03085-102	BARGE LOADING MARINE FACILITY — OPERATIONAL GEOMETRY	ISSUED FOR PERMIT	2019.07.18	D	
03085-103	BARGE LOADING MARINE FACILITY — MARINE DOLPHIN DETAILS	ISSUED FOR PERMIT	2019.07.18	D	
03085-104	BARGE LOADING MARINE FACILITY — CONVEYOR TRUSS & SUPPORT DETAILS	ISSUED FOR PERMIT	2019.07.18	D	







GENERAL NOTES FOR CIVIL WORKS:

I. GENERAL

- 1. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ALL REFERENCED DRAWINGS AND DOCUMENTS.
- 2. ALL MATERIALS AND CONSTRUCTION PROCEDURES SHALL BE IN ACCORDANCE WITH THE LATEST REVISION OF THE FOLLOWING CODES, STANDARDS, SPECIFICATIONS, INCLUDING ALL SUPPLEMENTS:
- PROVINCE OF BRITISH COLUMBIA OCCUPATIONAL HEALTH AND SAFETY REGULATIONS CSA A23.1 CONCRETE MATERIALS AND METHODS OF CONSTRUCTION
- CSA A23.3 DESIGN OF CONCRETE STRUCTURES
- THE AMERICAN SOCIETY OF TESTING MATERIALS—ASTM D698, D1556, D1557, C136
- NATIONAL BUILDING CODE OF CANADA
- 3. THE CONSTRUCTION DESIGN DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL RELATED PIPING, MECHANICAL, AND ELECTRICAL DOCUMENTS.
- 4. THE CONTRACTOR IS RESPONSIBLE FOR CHECKING AND VERIFYING ALL DIMENSION'S AND EXISTING SITE CONDITIONS INCLUDING ANY UNDERGROUND INTERFERENCES BEFORE EXCAVATION OR CONSTRUCTION BEGINS. THE CONTRACTOR SHALL REPORT ALL DISCREPANCIES AND INTERFERENCES.
- 5. THE CONTRACTOR SHALL PROVIDE AND TAKE RESPONSIBILITIES FOR ALL DEWATERING, SHORING AND TEMPORARY BRACING NECESSARY TO UNDERTAKE THE WORK IN A SAFE MANNER TO PROTECT LIFE, PROPERTY AND THE WORK AND ENSURE THAT ALL EXCAVATION ARE KEPT FREE OF WATER.
- 6. NOTWITHSTANDING THE USE OF APPROVED MATERIALS INDICATED ON THE DRAWINGS, ENGINEERS MAY AT ANY TIME REQUIRE THE CONTRACTOR TO PRODUCE CERTIFICATION BY AN INDEPENDENT TESTING AUTHORITY THAT THE MATERIALS USED CONFORM TO THE SPECIFIED STANDARDS.

II. SITE PREPARATION AND EARTHWORKS

- 1. ALL TOPSOIL, ORGANICS, VEGETATION AND OTHER DELETERIOUS MATERIALS SHOULD BE STRIPPED OFF FROM THE PROPOSED TRANSLOAD SITE AREA PRIOR TO CONSTRUCTION.
- 2. IF THE EXISTING SUBGRADE SURFACES AND/OR THE EXPOSED SUBGRADE SURFACES AFTER THE REQUIRED CUT ARE LESS THAN 0.6m BELOW THE DESIGN SUBGRADE SURFACE, THEY SHOULD BE SUB-EXCAVATED TO A DEPTH OF 0.6m BELOW THE DESIGN SUBGRADE SURFACE.
- 3. THE EXPOSED SURFACES SHOULD THEN BE BLADED, BACKFILLED AND COMPACTED USING SUITABLE MATERIALS. THE BACKFILL MATERIALS SHOULD BE PLACED IN LIFTS OF 0.3m, AND COMPACTED TO THE MINIMUM OF 98% OF STANDARD PROCTOR MAXIMUM DRY DENSITY (SPMDD), WITH THE EXCEPTION OF THE UPPER 0.3m WHICH SHOULD BE COMPACTED TO 100% SPMDD IN 0.3m LIFTS.
- 4. ANY BORROW MATERIAL REQUIRED AS ADDITIONAL FILL MUST CONSIST OF GRANULAR MATERIAL, PROVIDED IT IS FREE FROM ORGANICS, RUBBLE, SNOW, ICE, FROZEN LUMPS AND STONES GREATER THAN 150mm IN DIAMETER AND IS COMPACTED TO AT LEAST 98% OF STANDARD PROCTOR MAXIMUM DRY DENSITY (SPMDD) WITHIN 2% OF OPTIMUM MOISTURE CONTENT (OMC), WITH THE EXCEPTION OF THE UPPER 0.3m WHICH SHOULD BE COMPACTED TO 100% SPMDD.
- 5. FINISHED GRADE ELEVATIONS AS INDICATED ON THE CONSTRUCTION DRAWINGS REPRESENT THE TOP OF SURFACE AGGREGATE.
- 6. THE CONTRACTOR SHALL GRADE TO THE LEVELS, ELEVATIONS, CONTOURS AND MAKE NATURAL CHANGES TO BLEND SLOPES INTO LEVEL AREAS AS INDICATED ON THE CONSTRUCTION DRAWINGS.
- 7. PRIOR TO PERFORMING ANY WORK, THE CONTRACTOR SHALL VERIFY THE EXACT LOCATION OF ALL EXISTING UNDERGROUND SERVICES IN THE SURROUNDING AREA, HYDROVAC OR HAND EXCAVATION METHODS SHALL BE CARRIED OUT FOR FOUNDATIONS, PIPES, DUCTS & NEW STRUCTURES IN SUCH A MANNER AS TO PREVENT ANY DAMAGE TO THE EXISTING UNDERGROUND SERVICES. THESE ARE TO BE PROTECTED FROM LOADS IMPOSED DURING CONSTRUCTION.
- 8. CONTRACTOR SHALL BE RESPONSIBLE FOR THE STABILITY OF ALL EXCAVATION AT ALL TIMES AND SHALL ADHERE TO GEOTECHNICAL RECOMMENDATIONS, AND BRITISH COLUMBIA OCCUPATIONAL HEALTH AND SAFETY ACT REGULATIONS.
- 9. EXCAVATED MATERIALS WHICH ARE SUITABLE FOR FILL MATERIALS SHALL BE STOCKPILED IN DESIGNATED AREAS. CONTRACTOR SHALL ENSURE THAT THE SITE DRAINAGE PATTERNS ARE AS SHOWN ON THE CONSTRUCTION DRAWINGS AND ARE NOT TO BE ALTERED BY SUCH STOCKPILES.
- 10. ENSURE ADEQUATE RUN-OFF AND EROSION CONTROLS ARE IN PLACE TO PREVENT SILTATION OR ANY CONTAMINATION TO THE WATERSHED.
- 11. UNLESS SPECIFICALLY INDICATED OTHERWISE ON THE DRAWINGS, SITE FILL SHALL BE APPROVED IMPORTED FROST STABLE GRANULAR FILL SUBJECT TO TESTING BY AN INDEPENDENT GEOTECHNICAL TESTING LABORATORY AND TO THE SATISFACTION OF ENGINEER.

III. MATERIALS

- 1. SUBJECT TO THE APPROVAL OF THE GEOTECHNICAL ENGINEER; THE ON-SITE EXCAVATED SUBSOIL INORGANIC MATERIAL MAY BE SUITABLE FOR GENERAL BACKFILLING PROVIDED IT IS KEPT FREE OF ANY ORGANIC CONTENT, FROZEN MATERIALS AND ANY OTHER DELETERIOUS SUBSTANCE.
- 2. ALL MATERIALS SHALL BE FREE FROM LUMPS, FRIABLE OR SOLUBLE MATERIALS AND ORGANIC MATER.
- 3. COARSE SAND FOR BEDDING AND DRAINAGE SHALL CONFORM TO THE FOLLOWING GRADING:

SIEVE SIZE (mm) (SQUARE OPENING)	% PASSING (BY WEIGHT)				
10	100				
5	95-100				
2.5	80-100				
1.25	50-90				
0.630	25-65				
0.315	10-35				
0.160	2-10				
0.080	0-4				

* SAND SHALL BE COMPACTED IN LIFTS NOT EXCEEDING 300mm TO 98% OF SPMDD.

REVISIONS

4. THE PIT RUN GRAVEL AND FILL SAND SHALL BE OF SOUND, HARD FREE FROM FLAKES ORGANIC MATTER OR OTHER DELETERIOUS MATERIAL IN ACCORDANCE WITH THE SPECIFICATION AND THE SOIL REPORT AND SHALL MEET THE FOLLOWING REQUIREMENTS:

% PASSING BY WEIGHT

SIEVE SIZE (mm)	PIT RUN GRAVEL	FILL SAND
75.0	100	
25		100
5.0	20-50	75-100
0.630		45-80
0.080	2-8	2-10

- * PIT RUN GRAVEL SHALL BE PLACED IN COMPACTED LIFTS NOT EXCEEDING 300mm AND COMPACTED TO 100% OF SPMDD.
- 5. CRUSHED GRAVEL SHALL BE OF SOUND HARD PARTICLES, FREE FROM FLAKY PARTICLES, SOFT SHALE, ORGANIC OR ANY OTHER DELETERIOUS MATERIAL IN ACCORDANCE WITH SPECIFICATION EARTH WORK, THE SOIL REPORT, AND SHALL MEET THE FOLLOWING GRADATION REQUIREMENTS:

% PASSING BY WEIGHT

SIEVE SIZE (mm)	20mm CRUSH	40mm CRUSH
40		100
25		70-94
20	100	
16	84-94	55-85
10	63-86	44-74
5.0	40-67	32-62
1.25	20-43	17-43
0.630	14-34	12-34
0.315	9-26	8-26
0.160	5–18	5-18
0.080	2-10	2-10

* 20mm MINUS CRUSHED GRAVEL SHALL BE COMPACTED IN LIFTS NOT EXCEEDING 300mm TO 100% SPMDD.

IV. ROCK RIPRAP

- 1. MATERIAL FOR ROCK RIPRAP SHALL BE SOUND AND DURABLE FIELD STONE, OR ROUGH UNHEWN QUARRY STONE AS NEARLY RECTANGULAR AS PRACTICABLE, CONFORMING TO THE REQUIREMENTS OF THE FOLLOWING GRADATION:
 - 100% SMALLER THAN 450mm
 - AT LEAST 50% LARGER THAN 250mm
 - AT LEAST 90% LARGER THAN 150mm
- 2. THE ROCK RIPRAP SHALL BE WELL GRADED BETWEEN THE DIMENSIONS SPECIFIED ABOVE.

V. GRAVEL AND ASPHALT ROAD MATERIALS:

- 1. ROADS SHALL BE CONSTRUCTED TO LINES, GRADES, ELEVATIONS AND CROSS SECTIONS AS SHOWN ON CONSTRUCTION
- 2. ALL GRAVEL MATERIAL SHALL CONFORM TO THE GRADATION NOTES AND TABLES AS INDICATED IN SECTION III.
- 3. PAVED ROADS AS SPECIFIED ON THE CONSTRUCTION DRAWINGS SHALL BE PAVED WITH HOT LAID PLANT MIXED ASPHALT TO THE SPECIFIED THICKNESS SHOWN ON THE DRAWINGS. ALL MATERIALS, COMPOSITION AND PROPORTIONING, PAVING PLANT REQUIREMENTS, CONSTRUCTION METHODS, COMPACTION AND TESTING SHALL BE IN ACCORDANCE WITH THE SPECIFICATIONS AS NOTED ON THE CONSTRUCTION DRAWINGS.

VI. SEWER APPURTENANCES, DRAINS AND CLEANOUTS:

- 1. LOCATIONS, INVERT ELEVATION (INV. EL.), RIM ELEVATION (RIM EL.), BOTTOM OF BOX (B.O.B.) ELEVATIONS, HEIGHT (HT) & DIAMETERS (DIA.) OF SEWER APPURTENANCES (MANHOLE, CATCH BASIN, JUNCTION BOX, ETC.) SHALL BE BUILT AS INDICATED ON THE CONSTRUCTION DRAWINGS.
- 2. LOCATIONS, SIZES AND INVERT ELEVATIONS OF DRAINS AND CLEAN-OUTS SHALL BE BUILT AS INDICATED ON CONSTRUCTION DRAWINGS.
- 3. ALL SEWER APPURTENANCES SHALL BE SUPPORTED ON A MINIMUM 200mm CRUSHED GRAVEL OR SAND AS SPECIFIED IN THE CONSTRUCTION DRAWINGS.
- 4. BACKFILL AROUND SEWER APPURTENANCES BE FROST STABLE MATERIAL AS SPECIFIED IN THE CONSTRUCTION
- 5. ALL SEWER APPURTENANCES INCLUDING COVERS AND FRAMES SHALL BE ADEQUATE FOR CSW 600 WHEEL LOADING AS PER CSA S6 (SECONDARY ROADS) UNLESS NOTED OTHERWISE ON CONSTRUCTION DRAWINGS AND SHALL BE DESIGNED ON THE BASIS OF GROUND WATER TABLE AT GROUND SURFACE.
- 6. STEEL CORRUGATED PIPE (CSP) SIZES AND COVER SEE TABLE, ASSUMED NORMAL SITE CONDITION, PH > 6-8. MINIMUM RESISTIVITY > 9677 Ω -m.

CULVERT SIZE ID (mm)	CULVERT SIZE ID (IN)	MIN COVER (mm)
609	24	600
762	30	600
914	36	760
1066	42	760

NOTES


PERMIT AND ENGINEER STAMP





CIIMMTT


0:1	NUMBER	NO	J. ISSUE	DATE	BY CHK.D ENG APP.D	
10:42		А	ISSUED FOR 50% DESIGN	2017.AUG.15	MOH CT DM CT	EARTHWORKS
17 -10		Е	ISSUED FOR 90% DESIGN	2017.NOV.10	MOH CT DM CT	LOT 3, PLAN 13803 & BLOCK 9, PLAN 2602
-70 9-0		С	ISSUED FOR PERMIT	2018.MAY.29	MOH CT DM CT	
19 201		D	ISSUED FOR PERMIT	2018.JUN.15	MOH CT DM CT	NEW WESTMINSTER, BC
ED:		E	ISSUED FOR PERMIT	2019.JAN.09	MOH CT DM CT	DERWENT WAY TRANSFER STATION
SA		F	ISSUED FOR PERMIT	2019.JUL.18	MOH CT DM CT	GENERAL NOTES FOR CIVIL WORKS
PLOT						CADFILE 03082-01 DRAWING NO. REV.
4-1						SCALE N/A 03082-01 F


REFERENCE DRAWINGS


























GENERAL NOTES:

1. GENERAL

- 1.1 DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE. ELEVATIONS ARE IN METRES AND ARE REFERENCED
- 1.2 GEOTECHNICAL DESIGN IS BASED ON INFORMATION PROVIDED BY TETRA TECH LTD.

2. WATER LEVELS

DESIGN RIVER ELEVATIONS AT THE SITE ARE AS FOLLOWS (DFO): EXTREME HIGH WATER LEVEL (EHWL) HIGHER HIGH WATER LEVEL (HHWL) +1.8 m LOWER LOW WATER LEVEL (LLWL) -1.8 m

3. MAXIMUM BARGE SIZE DIMENSIONS

BARGE DWT = 3 100 TONNES HULL LENGTH = 67.0 m HULL WIDTH = 17.0 mHULL LOADED DRAFT = 1.62 m

4. DESIGN CODE

- 4.1 CANADIAN HIGHWAY BRIDGE DESIGN CODE (CAN/CSA S6-14)
- 4.2 WORKSAFE BC OCCUPATIONAL HEALTH AND SAFETY STANDARDS
- 4.3 BRITISH STANDARD BS639-4
- 4.4 UNIFIED FACILITIES CRITERIA (UFC) DESIGN: PIERS AND WHARVES (UFC 4-152-01)
- 4.5 PIANC (WORLD ASSOCIATION FOR WATERBORNE TRANSPORT INFRASTRUCTURE)

DESIGN LOADS

- 5.1 SELF-WEIGHT OF STRUCTURE COMPONENTS
- 5.2 MAINTENANCE ACCESS LOADS AS PER CL 3.8.10 OF CSA S6-14.
- 5.3 CONVEYOR MECHANICAL COMPONENTS
- 5.4 WIND LOADING TO CAN/CSA S6-14
- 5.5 SEISMIC DESIGN FOR THE ONSHORE TERMINAL WORKS ONLY. SEISMIC DESIGN HAS NOT BEEN CONSIDERED FOR THE MARINE STRUCTURES DESIGN (BERTHING DOLPHINS AND CONVEYOR SUPPORT PIER).
- 5.6 BERTHING LOADS
- 5.6.1 LARGEST VESSEL FULLY LADEN DISPLACEMENT = 3100 TONNES AT MAXIMUM BERTHING SPEED OF 0.33 m/s
- 5.7 MOORING LOADS
- 5.7.1 MOORING LOADS FROM WIND ARE BASED ON NOTE 5.4
- 5.7.2 MOORING LOADS FROM RIVER CURRENT ARE BASED ON MAXIMUM ANNUAL FRASER RIVER CURRENTS NOT INCLUDING ANNUAL FRESHET EVENTS.

6. MATERIALS

- 6.1 STEEL PIPE PILES TO BE ASTM A252 GRADE 3
- 6.2 ALL STEEL TO BE CSA G40.21M GRADE 350W
- 6.3 CAST-IN PLACE CONCRETE TO BE CSA A23.1 EXPOSURE CLASS C1, fc = 35 MPa AT 28 DAYS.
- 6.4 REINFORCING STEEL TO BE CSA G30.18M GRADE 400R

McElhanney McElhanney Consulting Services Ltd.


SCALE

1: 250



03082-100

	PERMIT AND ENGINEER STAMP	NOTES		REVISION	FERENCE DRAWINGS	RE
SUMMIT			DATE BY CHK'D ENG APP'D	NO. ISSUE	TITLE	NUMBER
EARTHWORKS —			2018.MAY.29 MOH CT CT	A ISSUED FOR PERMIT		
LOT 3, PLAN 13803 & BLOCK 9, PLAN 2602			2018.JUN.15 MOH CT CT	B ISSUED FOR PERMIT		
			2019.JAN.09 MOH CT CT	C ISSUED FOR PERMIT		
NEW WESTMINSTER, BC			2019.JUL.18 MOH CT CT	D ISSUED FOR PERMIT		
DERWENT WAY TRANSFER STATION						
BARGE LOADING MARINE FACILITY — GENERAL ARRANGEMENT						
CADFILE 03082-100 DRAWING NO. REV.		0 1:250 10				



FILE: C:\ODSI\TT - DERWENT\AUTOCAD\03082-102.DWG

— UNLOADED **BARGE**

HHWL EL. +1.8

VGEO03082-01

D

SUMMIT

EARTHWORKS

LOT 3, PLAN 13803 & BLOCK 9, PLAN 2602

NEW WESTMINSTER, BC

BARGE LOADING MARINE FACILITY OPERATIONAL GEOMETRY


DRAWING NO.

03082-102


03082-102

1:250


EL. +1.8



PLAN - TYPICAL DOLPHIN
SCALE 1: 50



ELEVATION - TYPICAL DOLPHIN SCALE 1: 50



McElhanney Consulting Services Ltd.



REFERENCE DRAWINGS		REVISIONS	NOTES	PERMIT AND ENGINEER STAMP		
NUMBER TITLE	NO. ISSUE A ISSUED FOR PERMIT	DATE BY CHK'D ENG 2018.MAY.29 MOH CT	1. PILES TO BE INSTALLED OPEN-ENDED BY COMBINATION OF VIBRATORY HAMMER AND IMPACT HAMMER PILE DRIVING METHODS			UMMIT EARTHWORKS —
	B ISSUED FOR PERMIT	2018.JUN.15 MOH CT	2. TOTAL PILE EMBEDMENT IS ANTICIPATED TO BE 15 M.			13803 & BLOCK 9, PLAN 2602
	C ISSUED FOR PERMIT D ISSUED FOR PERMIT	2019.JAN.09 MOH CT 2019.JUL.18 MOH CT	CT		NE	W WESTMINSTER, BC
						LOADING MARINE FACILITY
					CADFILE 03082-103	NE DOLPHIN — DETAILS DRAWING NO.
					SCALE AS NOTED	03082-103

